


IEC 60320 C-13 CONNECTORS

2 Pole 3 Wire Grounding

15 Ampere 250 Volt / 10 Ampere 250 Volt

“CE” MARK

IEC 60320 C-13



Description	Cat. No.	Approvals		
<p>Connector body. Right angle. Black thermoplastic, UL 94 V0. Compression (box type) terminals. Max. cord O.D. - External strain relief = 7 mm (0.276") Max. cord O.D.- Internal cord grip = 8 mm (0.315") Max conductor size accepted by terminals = 2.5 mm (14 AWG) Rating:15 Amp-250 Volt (UL/CSA),10 Amp-250 Volt (VDE) “CE” MARK</p>	57065-NS	3, 20, 22		
<p>Connector body. Right angle. Black thermoplastic, UL 94 V0. Compression (box type) terminals. Max. cord O.D. - External strain relief = 8.5 mm (0.335") Max. cord O.D.- Internal cord grip = 10 mm (0.394") Max conductor size accepted by terminals = 2.5 mm (14 AWG) Rating:15 Amp-250 Volt (UL/CSA),10 Amp-250 Volt (VDE) “CE” MARK</p>	57065-NSL	3, 20, 22		
<p>Connector body. Down angle. Black thermoplastic. Compression (box type) terminals. Max. cord O.D. - External strain relief = 8.5 mm (0.335") Max. cord O.D.- Internal cord grip = 9 mm (0.354") Max conductor size accepted by terminals = 2.5 mm (14 AWG) Rating: 10 Amp-250 Volt (VDE) “CE” MARK</p>	57070-A	2, 4, 7, 12, 13, 14, 17, 18, 22		

All dimensions are in millimeters (1 mm = 0.039")

Approvals: 1.ASTA 2.CEBEC 3.CSA 4.DEMKO 5.PSE(JET) 6.EANSW(DFT) 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO 14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI



© 2004 International Configurations, Inc. Entire contents of this catalog copyrighted. www.InternationalConfig.com

International Configurations, Inc. • P.O. Box 3374 • Enfield, Connecticut 06083 • TEL (860) 749-6380 • FAX (860) 749-2985 129