

IEC 60309 DEVICES, IP44, IP67 (4H)
2 Pole 3 Wire Grounding
 20 Amp 120 Volt A.C. - North American Rated
 C(UL)US LISTED

Yellow Color



E-mail: sales@internationalconfig.com
 Web site: www.internationalconfig.com



SPLASHPROOF IP44 **WATERTIGHT IP67**

DEVICE SPECIFICATION DOCUMENTS
 AVAILABLE ON OUR WEBSITE



888-21000-NS



888-2156-NS



888-31000-NS



888-3156-NS



888-13000-NS



888-1371-NS



888-1216-NS



888-1265-NS



888-110-NS



888-1132-NS



888-611316



888-71324-NS



888-6134-NS



999-613, 999-613-WP

Cable Mounting Plugs

888-21000-NS Splashproof Plug, IP44 Rated.

888-2156-NS Watertight Plug, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Cable Mounting Connectors

888-31000-NS Splashproof Connector, IP44 Rated.

888-3156-NS Watertight Connector, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Receptacles, Straight Type

888-13000-NS Splashproof Receptacle, IP44 Rated.

888-1371-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Receptacles, Angled Type

888-1216-NS Splashproof Receptacle, IP44 Rated.

888-1265-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Surface Mount Receptacles with Box

888-110-NS Splashproof Receptacle, IP44 Rated.

888-1132-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Surface Mount Inlets, Down Angled Type

888-611316 Splashproof Inlet, IP44 Rated.

888-71324-NS Watertight Inlet, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Inlet, Straight Type

888-6134-NS Splashproof Receptacle, IP44 Rated.

Nylon (Polyamide 6) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Plug and Inlet Closure Cap.

999-613 Color: Gray

999-613-WP Watertight Cap, IP67 Rated. Color: Gray

