

IEC 60309 DEVICES, IP44, IP67 (6H) 2 Pole 3 Wire Grounding

20 Amp 250 Volt A.C. - North American Rated
16 Amp 220-250 Volt A.C. - European Rated


Blue Color



E-mail: sales@internationalconfig.com

Web site: www.internationalconfig.com

UNIVERSAL
APPROVED



SPLASHPROOF IP44

WATERTIGHT IP67

DEVICE SPECIFICATION DOCUMENTS
AVAILABLE ON OUR WEBSITE



888-2126-NS



888-2126-NS-WT



888-3126-NS



888-3157-NS



888-13001-NS or 888-410306



888-1372-NS



888-1217-NS



888-1266-NS



888-111-NS



888-1133-NS



888-611306



888-71326-NS



888-6136-NS



999-613, 999-613-WP

Cable Mounting Plugs

888-2126-NS Splashproof Plug, IP44 Rated.

888-2126-NS-WT Watertight Plug, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Cable Mounting Connectors

888-3126-NS Splashproof Connector, IP44 Rated.

888-3157-NS Watertight Connector, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Receptacles, Straight Type

888-13001-NS Splashproof Receptacle, IP44 Rated.

888-410306 Splashproof Receptacle, IP44 Rated.

888-1372-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Receptacles, Angled Type

888-1217-NS Splashproof Receptacle, IP44 Rated.

888-1266-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Surface Mount Receptacles with Box

888-111-NS Splashproof Receptacle, IP44 Rated.

888-1133-NS Watertight Receptacle, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Surface Mount Inlets, Down Angled Type

888-611306 Splashproof Inlet, IP44 Rated.

888-71326-NS Watertight Inlet, IP67 Rated.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Panel Mount Inlet, Straight Type

888-6136-NS Splashproof Receptacle, IP44 Rated.

Nylon (Polyamide 6) Body. Color: Blue.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

Plug and Inlet Closure Cap.

999-613 Color: Gray

999-613-WP Watertight Cap, IP67 Rated. Color: Gray

