



IEC 60309 - CEE 17 IP67 Watertight Plugs

50/60 Hz	IEC 60309 BS 4343 SABS 1239 VDE 0623 DIN 49462/63								
	VOLTAGE	AMPS	POLES	GROUND POSITION	CATALOG NO.	STYLE NUMBER	DIMENSIONS		
							A	B	C
100/130 V	16 A	2 P + E	4H	999-2156	1	69	135	98.5	
100/130 V	32 A	2 P + E	4H	999-2168	1	91	175.5	124	
100/130 V	63 A	2 P + E	4H	999-2180	2	109	230	62	
100/130 V	125 A	2 P + E	4H	999-2190	2	124	295	72	
200/250 V	16 A	2 P + E	6H	999-2157	1	69	135	98.5	
200/250 V	16 A	3 P + E	9H	999-2160	1	77	147.5	111	
120/208-144/250 V	16 A	3 P + N + E	9H	999-2166	1	85	156	119.5	
200/250 V	32 A	2 P + E	6H	999-2169	1	91	175.5	124	
200/250 V	32 A	3 P + E	9H	999-2172	1	91	175.5	124	
120/208-144/250 V	32 A	3 P + N + E	9H	999-2178	1	98	175.5	130	
200/250 V	63 A	2 P + E	6H	999-2181	2	109	230	62	
200/250 V	63 A	3 P + E	9H	999-2184	1	113.5	271	204.5	
120/208-144/250 V	63 A	3 P + N + E	9H	999-2188	1	113.5	271	204.5	
200/250 V	125 A	2 P + E	6H	999-2191	2	124	295	72	
200/250 V	125 A	3 P + E	9H	999-2194	2	124	295	72	
120/208-144/250 V	125 A	3 P + N + E	9H	999-2198	1	131	311	236	
380/415 V	16 A	2 P + E	9H	999-2158	1	69	135	98.5	
380/415 V	16 A	3 P + E	6H	999-2161	1	77	147.5	111	
200/346-240/415 V	16 A	3 P + N + E	6H	999-2167	1	85	156	119.5	
380/415 V	32 A	2 P + E	9H	999-2170	1	91	175.5	124	
380/415 V	32 A	3 P + E	6H	999-2173	1	91	175.5	124	
200/346-240/415 V	32 A	3 P + N + E	6H	999-2179	1	98	175.5	130	
380/415 V	63 A	2 P + E	9H	999-0339	2	109	230	62	
380/415 V	63 A	3 P + E	6H	999-2185	2	109	230	62	
200/346-240/415 V	63 A	3 P + N + E	6H	999-2189	1	113.5	271	204.5	
380/415 V	125 A	2 P + E	9H	999-0439	2	124	295	72	
380/415 V	125 A	3 P + E	6H	999-2195	1	131	311	236	
200/346-240/415 V	125 A	3 P + N + E	6H	999-2199	1	131	311	236	

All dimensions are in millimeters (1 mm = 0.039")



STYLE No. 1



STYLE No. 2



© 2004 International Configurations, Inc. Entire contents of this catalog copyrighted. www.InternationalConfig.com

International Configurations, Inc. • P.O. Box 3374 • Enfield, Connecticut 06083 • TEL (860) 749-6380 • FAX (860) 749-2985 181