



**IEC 60309 - CEE 17**  
**IP 44 Splashproof Inlets**  
 Panel Mount, Angle Type

VOLTAGE	AMPS	POLES	GROUND POSITION	CATALOG NO.	STYLE NUMBER	DIMENSIONS								CLOSURE PLUG No.
						A	B	C	D	E	F	G	H	
100/130 V	16 A	2 P + E	4H	999-2705	2	74	70	85	56	56	5	-	121	999-613
100/130 V	32 A	2 P + E	4H	999-2758	2	95	90	111	70	56	5	-	160	999-623
100/130 V	63 A	2 P + E												
100/130 V	125 A	2 P + E												
200/250 V	16 A	2 P + E	6H	999-2706	2	74	70	85	56	56	5	-	121	999-613
200/250 V	16 A	3 P + E	9H	999-2709	2	75	70	88	56	56	5	-	126	999-614
120/208-144/250 V	16 A	3 P + N + E	9H	999-2756	1	85	85	100	70	70	6.2	6	141	999-615
200/250 V	32 A	2 P + E	6H	999-2759	2	95	90	111	70	56	5	-	160	999-623
200/250 V	32 A	3 P + E	9H	999-2762	2	95	90	111	70	56	5	-	160	999-623
120/208-144/250 V	32 A	3 P + N + E	9H	999-2768	1	85	85	115	70	70	6	6	158	999-625
200/250 V	63 A	2 P + E												
200/250 V	63 A	3 P + E												
120/208-144/250 V	63 A	3 P + N + E												
200/250 V	125 A	2 P + E												
200/250 V	125 A	3 P + E												
120/208-144/250 V	125 A	3 P + N + E												
380/415 V	16 A	2 P + E	9H	999-7139	2	74	70	85	56	56	5	-	121	999-613
380/415 V	16 A	3 P + E	6H	999-2751	2	75	70	88	56	56	5	-	126	999-614
200/346-240/415 V	16 A	3 P + N + E	6H	999-2757	1	85	85	100	70	70	6.2	6	141	999-615
380/415 V	32 A	2 P + E	9H	999-7239	2	95	90	111	70	56	5	-	160	999-623
380/415 V	32 A	3 P + E	6H	999-2763	2	95	90	111	70	56	5	-	160	999-623
200/346-240/415 V	32 A	3 P + N + E	6H	999-2769	1	85	85	115	70	70	6	6	158	999-625
380/415 V	63 A	2 P + E												
380/415 V	63 A	3 P + E												
200/346-240/415 V	63 A	3 P + N + E												
380/415 V	125 A	2 P + E												
380/415 V	125 A	3 P + E												
200/346-240/415 V	125 A	3 P + N + E												

All dimensions are in millimeters (1 mm = 0.039")



STYLE No. 1



STYLE No. 2

© 2004 International Configurations, Inc. Entire contents of this catalog copyrighted. www.InternationalConfig.com

